

60-W

Water-Based Sealer/Primer/Coating

DESCRIPTION

60-W can be used as a primer or concrete sealer on old or “green” concrete and is often used as a primer for other Absolute Protective Coatings systems.

Ready for light traffic in 8-12 hours.

RECOMMENDED USES

- ✓ Concrete Sealer (including green concrete)
- ✓ Primer
- ✓ Decorative Coating
- ✓ Concrete Curing Agent



60-W

Water-Based Sealer/Primer/Coating

1265 N Hendrickson Dr
Tel:360-673-6404

PERFORMANCE DATA

Pot Life

1 hour @ 70° F

Initial Set, Light Traffic

8-12 hours @ 70° F

Heavy Traffic

24 hours @ 70° F

Cure Temp Limit

50° F (minimum)

Re-coat Window

2 - 24 hours, see specification

Coverage

250-400 square feet per gallon
**Depending upon porosity of concrete an additional coat may be required on porous concrete or wood.*

Colors

Clear, other colors available by request

Packaging

1 gallon kit (yields 1.5 gallons)
3 gallon kit (yields 4.5 gallons)

Shipping Weight

10 lbs/gallon (approximate)



PRODUCT OVERVIEW

60-W is a unique water-based epoxy resin system for use as a primer to promote adhesion for subsequent coating systems, a sealer to mitigate moisture vapor transmission on concrete substrates, and as a low-cost decorative coating.

60-W is also used as a curing agent on freshly placed (green) concrete. It can also be used as a primer or concrete sealer on old or "green" concrete. Available in clear for sealer and curing applications; a variety of colors are available for low-cost decorative finishes.

TYPICAL USAGE AND APPLICATIONS

60-W is a usage proven product in a variety of applications such as manufacturing plants, warehouses, mechanical plants, electrical plants and various other applications in commercial and industrial uses.

60-W may be applied by roller, brush or low-pressure sprayer and is widely used as a quality concrete sealer, even when used on "green" concrete. 60-W also serves as an excellent primer for other Absolute Protective Coatings systems.

For a demonstration of 60-W in your area, please call us at 360-673-6404 or send a note to absoluteconcretecolors@gmail.com

RECOMMENDED READING

MSDS [Material Safety]
Product Data Sheet

Available online at
absoluteconcretecolors.net

Recommendations for product use based on tests believed to be reliable. Field conditions vary widely. For this reason, the user must determine product suitability for the particular use and specific applications. Absolute Concrete Colors. assumes no liability for injury, loss or damage resulting from use of this product. This product is not intended for retail distribution and should only be used by construction professionals experienced in the application and handling of potentially hazardous chemical compounds.